

Claim Amendments

10.(currently amended) An HF right-angle connector comprising a plug receiver, on which a key for ~~the~~ a plug to be received is disposed, and a socket housing, in which connecting means for a coaxial cable are accommodated, wherein the plug receiver ~~is mountable in various positions onto the socket housing and wherein~~ has a latching device for securing the plug to be received ~~is disposed on the plug receiver, and the plug receiver being~~ is mountable in one of three different positions on the socket housing, so that the latching device is disposed either to the left of the socket housing or to the right or at ~~the~~ an end face of the socket housing.

11.(currently amended) The HF right-angle connector according to claim ~~12~~ 10, wherein the latching device constitutes the key for the plug to be received.

12.(currently amended) The HF right-angle connector according to claim ~~12~~ 10, wherein keying grooves/ribs are provided in the plug receiver which cooperate with corresponding keying ribs/grooves on the plug to be received.

13.(currently amended) The HF right-angle connector according to claim ~~12~~ 10, wherein a middle part is disposed on the connecting side of the plug receiver to the socket housing, which is smaller than the area of the plug receiver, and a plate is disposed on the middle part, which projects laterally on all sides beyond the middle part, and opposing U-shaped receivers are formed on the socket housing, into which the plate is insertable.

14.(currently amended) The HF right-angle connector according to claim ~~15~~ 13, wherein the plate is substantially square and is provided with recesses for the cable routing.

15.(currently amended) The HF right-angle connector according to claim ~~15~~ 13, wherein latching means are provided on the plug receiver and counterpart latching means are provided on the socket housing.

16.(currently amended) The HF right-angle connector according to claim ~~17~~ 15 wherein the latching means comprises ~~of~~ projections on the middle part, and the counterpart latching means comprises recesses in the socket housing.

17.(currently amended) The HF right-angle connector according to claim ~~12~~ 10 wherein the latching device on the plug receiver comprises ~~of~~ a latching hook, which is manually releasable by means of a button.

18.(currently amended) The HF right-angle connector according to claim ~~12~~ 10 further comprising an insulation displacement connection for connecting to an external conductor and a crimp connection for connecting to an internal conductor.